

## **AMENDMENTS TO THE CLAIMS**

This listing of claims will replace all prior versions, and listings, of claims in the application:

### **Listing of Claims:**

1. (Currently Amended) A motor mounting platform for use in an appliance comprising:

the motor mounting platform constructed of a first material;

at least two brush holders constructed of a second material being engaged to the motor mounting platform; and

at least one motor support mounted to the motor mounting platform, wherein the motor mounting platform is not in electrical contact with any current carrying component when the motor is attached to the at least one motor support.

2. (Original) The motor mounting platform of claim 1 wherein the second material is electrically non-conductive.

3. (Original) The motor mounting platform of claim 1 wherein the first material has a lower thermal classification than the second material.

4-26. (Cancelled)

27. (Withdrawn) In combination, a motor mounted to a motor mounting platform having a hole, the motor having a shaft extending therethrough, the motor mounting platform comprised of:

- at least one motor support mounted to the platform;

- at least two pair of brush holder guides mounted directly to the platform;

- at least two brush holders constructed of electrically non-conductive material, the at least two brush holders each removably engaged to the platform within a pair brush holder guides, the brush holders comprised of:

  - a commutating brush positioned within an opening in the brush holder, the commutating brush having a first end and a second end with the first end being capable of contacting a commutator of a motor;

  - a wire located within the opening, the wire attached to the second end of the commutating brush;

  - a spring positioned between the second end of the commutating brush and the second end of the brush holder, the spring encircling the wire; and

  - a terminal located in the second end of the brush holder opposite the commutating brush, and in contact with the wire.

28. (Withdrawn) The combination of claim 27 wherein the commutating brush is constructed of carbon.

29. (Withdrawn) A method for manufacturing a commutator brush assembly having a commutating brush within a commutator brush holder, the method comprising the steps of:

providing a commutator brush holder having an opening between a first end and a second end in which the opening receives a commutator brush and a top side having a first slot therealong in communication with the opening; and

positioning a lead wire for connecting to the commutator brush through the first slot.

30. (Withdrawn) The method of claim 29 further comprising:

connecting a first end of a lead wire to a terminal lead;

encircling the lead wire with a spring;

securing a second end of the lead wire to an end of the commutating brush;

placing the commutating brush within the opening at the first end of the commutator brush holder such that the lead wire is aligned within the first slot;

sliding the lead wire along the length of the first slot; and

securing the terminal lead to the brush holder.

31. (Withdrawn) The method of claim 29 further comprising the step of:

providing a second slot in the top side, the second slot in communication with the opening and perpendicular to the first slot; and

securing the terminal lead within the second slot.

32. (Withdrawn) The method of claim 31 further comprising sliding the lead wire along the length of the first slot until reaching the second slot.

33. (Withdrawn) The method of claim 31 wherein the second slot is adjacent to the second end of the brush holder.

34. (Currently Amended) The motor mounting platform of claim 1 wherein:  
the motor mounting platform has a first side and a second side in which  
the second side includes a cavity surrounded by ~~an edge~~ a wall.
35. (Previously Presented) The motor mounting platform of claim 34 wherein at least one motor support is mounted on the first side.
36. (Previously Presented) The motor mounting platform of claim 34 wherein the brush holder is mounted on the first side.
37. (Previously Presented) The motor mounting platform of claim 34 wherein the cavity has an involute shape.
38. (Previously Presented) The motor mounting platform of claim 1 wherein an exhaust outlet extends from the mounting platform.
39. (Currently Amended) The motor mounting platform of claim 38 wherein the exhaust outlet is integrally molded with the motor mounting platform.
40. (Cancelled)
41. (Currently Amended) The motor mounting platform of claim 40 1 wherein the motor support includes a first post and a second post.
42. (Currently Amended) The motor mounting platform of claim 41 wherein the first and second post are mounted on opposing sides of a hole defined in and extending through the motor mounting platform.
43. (Cancelled) The motor mounting platform of claim 40 wherein a motor is attached to the at least one motor support positioning the mounting platform out of electrical contact from the motor.

44. (Currently Amended) The motor mounting platform of claim 1 ~~includes~~ further comprising at least two pair of brush holder guides mounted directly to the motor mounting platform in which each pair receivably engages one of the brush holders and is adapted to permit the brush holder to be removed from the motor mounting platform.

45. (Currently Amended) The motor mounting platform of claim 44 wherein each pair of brush holder guides comprises a pair of inverted L-shaped guides, each L-shaped guide opposing the other.

46. (Currently Amended) The motor mounting platform of claim 44 wherein a stop bar is mounted ~~into~~ to the motor mounting platform between each pair of brush holder guides and proximate a hole which extends through the platform.

47. (Previously Presented) The motor mounting platform of claim 44 wherein the brush holder is comprised of:

- a housing having an opening extending lengthwise between a first end and a second end;

- a top side including a first slot in communication with the opening and a second slot in communication with the opening positioned perpendicular to the first slot;

- a bottom side opposite the top side; and

- a first side and a second side opposite of each other and perpendicular to both the first and second ends and the top and bottom sides.

48. (Previously Presented) The motor mounting platform of claim 47 wherein:

- the first side and the second side of the brush holder are a first length;

- the first end and the second end of the brush holder are a second length; and

- the first length is longer than the second length.

49. (Previously Presented) The motor mounting platform of claim 47 wherein:

the top side of the brush holder has a first width;

the bottom side of the brush holder has a second width; and

the second width is greater than the first width.

50. (Previously Presented) The motor mounting platform of claim 47 wherein the first and second sides of the brush holder each have a bottom edge adapted to be positioned within a pair of brush holder guides.

51. (Previously Presented) The motor mounting platform of claim 47 wherein the bottom side includes a notch capable of engaging a stop bar.

52. (Previously Presented) The motor mounting platform of claim 47 wherein the brush holder is further comprised of:

a commutating brush positioned within the opening, the commutating brush having a first end and a second end with the first end being capable of contacting a commutator of a motor;

a wire attached to the second end of the commutating brush;

a spring contacting the second end of the commutating brush and encircling the wire; and

a lead located in the second end of the brush holder, the lead contacting the wire and the spring.

53. (Previously Presented) The motor mounting platform of claim 52 wherein the commutating brush is constructed of carbon.

54. (Currently Amended) The motor mounting platform of claim 44 wherein ~~a~~ the at least one motor support and the brush holder guides are integrally molded with the motor mounting platform.

55. (Currently Amended) The motor mounting platform of claim 54 wherein the at least one motor support contacts at least one brush holder guide.

56. (Previously Presented) The motor mounting platform of claim 1 wherein a wire guide is connected to the motor mounting platform.

57. (New) A motor mounting platform for use in an appliance comprising:  
the motor mounting platform constructed of a first material;  
at least two brush holders constructed of a second material being engaged to the motor mounting platform;  
at least one motor support mounted to the motor mounting platform; and  
at least two pair of brush holder guides mounted directly to the motor mounting platform in which each pair receivably engages the brush holders and is adapted to permit the brush holders to be removed from the motor mounting platform.

58. (New) The motor mounting platform of claim 57 wherein each pair of brush holder guides comprises a pair of inverted L-shaped guides, each L-shaped guide opposing the other.

59. (New) The motor mounting platform of claim 57 wherein a stop bar is mounted to the motor mounting platform between each pair of brush holder guides and proximate a hole which extends through the platform.

60. (New) The motor mounting platform of claim 57 wherein the brush holder is comprised of:

a housing having an opening extending lengthwise between a first end and a second end;

a top side including a first slot in communication with the opening and a second slot in communication with the opening positioned perpendicular to the first slot;

a bottom side opposite the top side; and

a first side and a second side opposite of each other and perpendicular to both the first and second ends and the top and bottom sides.

61. (New) The motor mounting platform of claim 60 wherein the first and second sides of the brush holder each have a bottom edge adapted to be positioned within a pair of brush holder guides.

62. (New) The motor mounting platform of claim 60 wherein the bottom side includes a notch capable of engaging a stop bar.

63. (New) The motor mounting platform of claim 57 wherein the at least one motor support and the brush holder guides are integrally molded with the motor mounting platform.

64. (New) The motor mounting platform of claim 57 wherein the motor mounting platform is not in electrical contact with any current carrying component when the motor is attached to the at least one motor support.



65. (New) A motor mounting platform for use in an appliance, comprising:  
the motor mounting platform constructed of a first material;  
at least two brush holders constructed of a second material being engaged to the  
motor mounting platform; and  
at least one motor support integrally molded with the motor mounting platform.
66. (New) The motor mounting platform of claim 65, further comprising at least two  
pair of brush holder guides mounted directly to the motor mounting platform in which each pair  
receivably engages the brush holders and is adapted to permit the brush holders to be removed  
from the motor mounting platform.
67. (New) The motor mounting platform of claim 65, wherein the motor mounting  
platform is not in electrical contact with any current carrying component when the motor is  
attached to the at least one motor support.